



Operations Manual

Item: M2100 (-E)

V1.0

TubeRocker

See Saw Rocker



Introduction:

Benchmark's TubeRocker Mini is compact, quiet rockers whose speed and tilt angle have been optimized for sample mixing. The rocker can also be used for general purpose lab mixing with a full 1.5kg (3.2 lbs) load capacity. The rocker will operate in cold rooms down to 4°C and in incubators up to 65°C.

I. Specifications:

Speed: Fixed at 24 RPM (20rpm for 230V models)

Tilt angle: +/-30 degrees from horizontal

Motor: Electronically controlled brushless gear motor (no carbon brushes to replace)

Platform: 30.0 x 11.4 cm (12" x 4.5")

Load Capacity: 1.5kg (3 lbs) centered and balanced

Dimensions: wxdxh 33.6x13.5x10 cm

Weight: 2kg (4lbs)

Mat: Grooved tube mat, autoclavable

Electrical: 115VAC, 60Hz, 0.4 amps (BR1000)

230VAC, 50Hz, 0.2 amps (BR1000-230)

Operating environment: 4°C (cold room) to 45°C

Warranty: 2 years

II. Product Set-Up:

Place the rocker on a clean, flat, stable surface. Make sure that the power switch is in the OFF (not illuminated) position. Plug the rocker into a properly grounded outlet. Check that nothing blocks the up and down rocking action of the platform.

III. Product Operation:

Load the platform from the center out, making sure the items placed on the platform create a balanced load around the center line of the platform. This is important as large, overhung platform loads may

cause the rocker to tip over. Turn the unit on by activating the ON/OFF switch so that it is illuminated.

IV. Care and Maintenance:

No routine maintenance is required other than to keep the unit clean. Cleaning can be done with a damp cloth. Avoid the use of solvents as they may damage the product housing.

Service and Contact:

In the event that service or technical support is required, please contact **Benchmark** by phone at **1-908-769-5555** or by email at info@benchmarkscientific.com.



P.O. Box 709 Edison, NJ 08817 USA
Ph: 908-769-5555 EM: info@BenchmarkScientific.com